

Part Number: 1780480

Product Description: BASERACK LIGHTBAR MNT DOVETAIL

WARNING

- This mount kit is designed to mount LED light bars up to 3.5kg/7.7lb in weight, with a single, side mount bolt. Fasteners for light bar not included
- Do not use this product for any product, other than those specified by ARB
- This product must be installed exactly as per these instructions using only the hardware supplied
- This product or its fixing must not be modified in any way
- These instructions are correct as at the publication date
- During installation, it is the duty of the installer to check correct operation/clearances of all components
- Work safely at all times
- Unless otherwise instructed, tighten fasteners to specified torque
- Fastener torques are to be checked at regular intervals

ARB 4x4 ACCESSORIES

Corporate Head Office

www.arb.com.au

42-44 Garden St Kilsyth, Victoria AUSTRALIA 3137 Australian enquiries North & South American enquiries Other international enquiries Tel: +61 (3) 9761 6622 Fax: +61 (3) 9761 6807

> sales@arb.com.au sales@arbusa.com exports@arb.com.au

REQUIRED TOOLS FOR FITMENT OF PRODUCT:

13mm Spanner/Wrench

FASTENER TORQUE SETTINGS:				
SIZE	Torque Nm	Torque lbft		
M8	22Nm	16lbft		

PARTS LISTING				
APPLICATION.	PART NO.	QTY	DESCRIPTION	
	3750752R	1	BRKT LIGHT BAR MNT DTAIL SIDE RH	
	3750752L	1	BRKT LIGHT BAR MNT DTAIL SIDE LH	
	3752563	2	BRKT ACC CLAMP 40MM	
	6151921	2	BOLT COHD M8x20 PC8.8 LWHD	
Ô	6151223	2	NUT NYLOC M8 BLACK	
0	4584378	2	WASHER M8x19x1.2mm BLACK	

FITTING PROCEDURE			
	1.	Assemble brackets with an M8 bolt, washer and nut Only tighten nuts 3-4 turns	
	2.	 Plan mounting The bracket can mount flange up or flange down Check clearance distance to vehicle panels Check door opening Check window opening 	
	3.	Fit one bracket to each end of the light bar as shown (hardware to light not supplied)	
	4.	Fit the mounting brackets over the dovetail	
P P P P P P P P P P P P P P P P P P P	5. 6.	Tighten the light bar bolts to manufactures recommendation Tighten the supplied M8 COHD bolts to specified torque	

